

Push Up Counter Shutter Instructions



Power driver with 6" Phillips #2 tip is best tool to install the shutter.



Parts of the shutter with face cover removed. Screws and other small parts are provided.



1 Remove casing from jamb if present. Shutter needs to be mounted on a flat surface.



2. Remove protective film from box covers.




3. Slip rails onto end cap locator legs.



4. Rail totally on locator leg.



5. Set rails and storage box to the wall location.
Always support box until attached to wall or
 the locator legs can break. They are not load bearing.



6. Attach the rails to the wall.



7. Spin axle in direction of shutter going down () turns.
 Number of turns depends on shutter height.
 Check information on shutter roll.
 Turning the wrong way will cause torsion spring to detach.



8. Unwrap slat from axle and hang outside of rails.
 Attach balance of slat bundle and raise shutter.



9. Remove dead bolts if installed and raise shutter completely.
 Lower slat into rails.



10. Form side of rail by pushing top sideways 1/8"



11. Form front rail guide.
Use channel lock pliers to bend front ear of rail forward 30 degrees.
This forms a guide for the slat to enter the rails.



12. Reinstall dead bolts and add stops to keep shutter from going into box cover when raised.
Check operation of shutter.



13. Attach face cover.



14. Install rail hole plug buttons.